



digital SERIES

TIG200DC PFC SPECIFICATIONS

The R-Tech TIG200DC PFC is a 200A DC TIG welder with 240V input, electronic HF starting, fully featured pulse welding, slope up/down, twin LED display, high duty cycle and foot pedal option



FEATURES & SPECIFICATIONS

Full function digital control panel designed for easy use - control all setup and machine parameters from a single button - Easy start and finish set-up.

- Power Factor Correction - Gives lower running costs and higher energy efficiency, cleans noisy power supplies & is 100% generator friendly
- Amperage Range: 5 to 200 Amps (TIG)
- Amperage Range: 10 to 150 Amps (Stick)
- Electronic HF - improved arc starting and less interference
- 100% Duty Cycle at 40°C: 35%
- Pulse width: 0.1-1.0s
- Fuse Rating: 16 Amps
- Pulse Frequency: 0.5-10Hz
- No-Load Voltage: 62 Amps
- Dimensions: 400 x 170 x 325 mm Weight: 10kg
- VRD Voltage Reduction in MMA - reduces OCV in standby for increased user safety
- Full 4-way functioning with control of pre/post flow gas, initial/final amps, slope up/down
- Generator Friendly - Recommended minimum size: 6KVA
- Dual LED displays for preset and actual amps
- MMA Anti-Stick & Hot Start technology
- Remote Foot Pedal Option
- Package includes: WP26 TIG torch (4m), earth lead & clamp, gas hose, regulator & owners manual

3 Year Warranty



www.weld-tech.co.za
sales@weld-tech.co.za

ORDER BY PHONE
+27117840171